4-Wheel

Weight Capacity	325 lbs.
Maximum Speed ¹	Up to 4 mph
Ground Clearance ³	1.4" at motor, 1.5" at anti-tip, 3.5" (side deck)
Turning Radius ³	38.25"
Overall Length ³	45.75"
Overall Width ³	20"
Seat-to-Ground Height	21.5"- 23.5"
Seat-to-Deck Height	16"-18"
Front Tires	2" x 7" solid
Rear Tires	2.5" x 9" solid
Suspension	Front and rear (CTS Suspension)
Range Per Charge 1,2	Up to 13.4 miles (200 lbs.) Up to 11.6 miles (325 lbs.)
Total Weight Without Batteries ⁵	120 lbs.
Heaviest Piece When Disassembled ³	48 lbs. (rear section)
Standard Seating	Type: Foldable, compact, molded plastic Weight: 27 lbs. Material: Black vinyl Dimensions: Width: 17", Depth: 17"
Drive System	24-volt DC motor, rear-wheel drive, two-motor
Dual Braking System	Regenerative and electromechanical
Battery Requirements ^{4,6}	Size: (2) 22 AH Weight: Battery box 31.5 lbs. 13.5 lbs. each
Battery Charger	Off-board, 3.5 amp
Warranty	Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Battery: 6-months

HCPCS Code: K0899

POWER MOBILITY DEVICE, NOT CODED BY DME PDAC OR DOES NOT MEET CRITERIA

1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a

- variance of (+ or -) 10%. 2 Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 4 Battery weight may vary based on battery manufacturer.
- 5 Includes standard seat weight.
- 6 AGM or gel cell type required.



(US) 800-800-8586 • (Canada) 888-570-1113

pridemobility.com







HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.



NAVIGATE TIGHT CORNERS AND SMALL SPACES **EFFORTLESSLY**



Curb light, front LED lights, and rear lights

CTS Suspension for greater comfort



USB charger built into tiller



Front LED lights



Patent-pending, intelligent-turning, iTurn Technology™

Get the 4-wheel scooter with a 3-wheel turning radius with the **Zero Turn 8** and Pride's patent-pending, intelligent-turning, iTurn Technology™. Navigate tight corners and small spaces effortlessly with a 38.25" turning radius. Illuminate your ride with bright LED lighting. Dual motors and CTS suspension ensure a smooth and comfortable drive.

- The first 4-wheel indoor scooter.
- Charging port built into the tiller for easy charging of the scooter
- Contemporary rim design makes the Zero Turn 8 look as good as it drives
- Dual motors for added traction in rough terrain
- USB charger built into the tiller for convenient charging of smart phones and portable devices

Available Colors











Green Opal

Moonstone* Black

Onvx

Pearl White

Pewter Sapphire Blue

Options

• 22 AH battery box (additional spare)

Accessories*

- Back mounted accessories. - Rear basket
- Oxygen holder
- Cell phone holder
- Cup holder
- Double rear mount, 3"
- Forearm crutch holder
- 50" lap belt
- Micro, black, weather cover
- Rear view mirror
- Saddlebag
- Safety flag
- Single rear mount, 3"
- Walker holder
- Wishbone crutch holder
- Under seat storage

Military Patches



*Only one rear accessory can be used at a time.